

# SSJ SERIES KEYED SAFETY SHEAR JOINT

The SSJ Series shear safety joint (SSJ) provides for an emergency release of the tubing string. A straight pull separates the tool at a predetermined shear value as set by inserting or removing shear screws. The SSJXXA Series keyed shear safety joint allows torque to be transmitted through the tool without affecting the shear screws.

TUBING SIZE	MAX O.D.	MIN I.D.	THREAD CONNECTION	PRODUCT NUMBER
	Nom. Standard *	Nom. Standard *		
1.660	2.22"	1.22"	1.660 EUE 10rd	SSJ12A
1.900	2.50	1.43	1.900 EUE 10rd	SSJ15A
2-3/8	3.06	1.87	2-3/8 EUE 8rd	SSJ20A
2-7/8	3.68	2.37	2-7/8 EUE 8rd	SSJ25A
3-1/2	4.50	2.87	3-1/2 EUE 8rd	SSJ30A

\* All dimensions are for general reference only and subject to change; verify exact dimensions at the time of purchase order.



Stren Technology Solutions - Houston Mfg Plant - 419 Century Plaza Dr. - Houston, Texas 77073-6028  
 Phone: (281) 951-3000 - FAX: (281) 820-5909 - Website: [www.stren.net](http://www.stren.net) - Email: [sales@stren.net](mailto:sales@stren.net)